



Gator Prime Self Priming Pump

Model: GP-12

Size: 12" x 12"

Model: GP-12



GATOR PRIME
GP-12 DATA SHEET

Data Sheet

Net Weight 998kg (2200lbs)
Shipping Weights 1066kg (2350lbs)
Impeller Dia. 457,2mm (18")
R.P.M. from 650rpm to 1250rpm
Max. Solids 76mm (3")

Self Priming

650 rpm 1,6m (5ft) - 750 rpm 2,7m (9ft)
850 rpm 3,9m (13ft) - 950 rpm 4,5m (15ft)
1050 rpm 4,9m (16ft) -1150 rpm 4,9m (16ft)
1250 rpm 4,9m (16ft)

Construction

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30
ALL CARBON STEEL SHAFTS ARE SAE 140 HT
ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL,
CD4, DIN 1-443
ALL PARTS LABELED 31SS ARE CFM
EPOXY AND CERAMIC COATINGS ARE AVAILABLE
THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY,
VITON O-RINGS AND TUNGSTEN CARBIDE FACES



THOMAS PUMP-SLIDELL

120 INDUSTRIAL DR.
SLIDELL, LA 70460
985-649-3000 / 985-649-4300 FAX

THOMAS PUMP-GEORGIA

105 ENTERPRISE AVE.
CARROLLTON, GA 30117
770-908-8000 / 770-908-8008 FAX